

## S-DES (simplified Data Encryption Standard) Assignment template:

**ENCRYPTION TEMPLATE**

<p>To the input (plaintext), apply initial permutation IP:</p> <table border="1" data-bbox="155 478 568 579"> <tr> <th colspan="8">IP</th></tr> <tr> <td>2</td><td>6</td><td>3</td><td>1</td><td>4</td><td>8</td><td>5</td><td>7</td></tr> </table> <p>In the next steps, we will develop 4 bits with which to replace the left half of this "blue" result.</p>	IP								2	6	3	1	4	8	5	7	<p>Input:</p> <p>_____</p> <p>_____</p>
IP																	
2	6	3	1	4	8	5	7										
<p>To right 4 bits of above result, apply expansion/permutation E/P (generating 8 bits from 4). The bit numbering is that of the 4-bit right-nibble, not of the 8-bit byte (e.g., indicated bit 2 refers to byte's bit 6).</p> <table border="1" data-bbox="155 982 568 1083"> <tr> <th colspan="8">E/P</th></tr> <tr> <td>4</td><td>1</td><td>2</td><td>3</td><td>2</td><td>3</td><td>4</td><td>1</td></tr> </table>	E/P								4	1	2	3	2	3	4	1	<p>_____</p>
E/P																	
4	1	2	3	2	3	4	1										
<p>Upon above result, perform binary XOR operation with subkey K1:</p> <table border="1" data-bbox="155 1236 568 1337"> <tr> <th colspan="8">K1</th></tr> <tr> <td>1</td><td>0</td><td>1</td><td>0</td><td>0</td><td>1</td><td>0</td><td>0</td></tr> </table>	K1								1	0	1	0	0	1	0	0	<p>_____</p>
K1																	
1	0	1	0	0	1	0	0										
<p>Determine a row and a column from above XOR result. For the row, combine bits 1 and 4 and convert to decimal. For the column, combine bits 2 and 3 and convert to decimal.</p> <p>Determine another row and column. For this second row, combine bits 5 and 8; for this second column, bits 6 and 7.</p> <p>Identify the entry in s-box S0 at the first row/first column you determined. S0 shows it in decimal; convert it to binary (two bits). Enter those bits as the first</p>																	

half of the 4-bit number at right.

Identify the entry in s-box S1 at the second row/second column you determined. Convert it to binary; enter those two bits as the second half of the number at right.

S0 =		c0	c1	c2	c3
	r0	1	0	3	2
	r1	3	2	1	0
	r2	0	2	1	3
	r3	3	1	3	2

\_\_\_\_\_

S1 =		c0	c1	c2	c3
	r0	0	1	2	3
	r1	2	0	1	3
	r2	3	0	1	0
	r3	2	1	0	3

To above result, apply permutation P4:

P4			
2	4	3	1

\_\_\_\_\_

Upon the above P4 result, perform binary XOR operation, combining it with the left 4-bits of our first result (application of IP to original plaintext input, blue cell above).

\_\_\_\_\_

We are trying to replace the left half of that first result. These XOR result bits are the replacement bits for it.

Rewrite that "blue" first result with its left half replaced. (Look it up,

keep/copy its right half, use the preceding result as the new left half.)

\_\_\_\_\_

Swap the two 4-bit halves of the above (previous) result.

In the next steps, we will again develop 4 replacement bits, and with them replace the left half of this "green" swap result. The steps will be the same ones used for that purpose already.

\_\_\_\_\_

To right 4 bits of above swap result, apply expansion/permutation E/P (generating 8 bits from 4):

E/P							
4	1	2	3	2	3	4	1

\_\_\_\_\_

Upon above result, perform binary XOR operation with subkey K2:

K2							
0	1	0	0	0	0	1	1

\_\_\_\_\_

Determine a row and a column from above result. For the row, combine bits 1 and 4 and convert to decimal. For the column, combine bits 2 and 3 and convert to decimal.

Determine another row and column. For this second row, combine bits 5 and 8; for this second column, bits 6 and 7.

Identify the entry in s-box S0 at the first row/first column you determined. It's given in decimal; convert it to binary (two bits). Enter those bits as the first half of the 4-bit number at right.  
Identify the entry in s-box S1 at the second row/second column you

determined. Convert it to binary; enter those two bits as the second half of the number at right.

S0 =		c0	c1	c2	c3
	r0	1	0	3	2
	r1	3	2	1	0
	r2	0	2	1	3
	r3	3	1	3	2

\_\_\_\_\_

S1 =		c0	c1	c2	c3
	r0	0	1	2	3
	r1	2	0	1	3
	r2	3	0	1	0
	r3	2	1	0	3

To above result, apply permutation P4:

P4			
2	4	3	1

\_\_\_\_\_

Upon the above P4 result, perform binary XOR operation, combining it with the left 4-bits of the earlier swap result (green cell above).

We are trying to replace the left half of that swap result. These XOR result bits are the replacement bits for it.

\_\_\_\_\_

Rewrite that "green" swap result with its left half replaced. (Look it up, keep/copy its right half, use the preceding result as the new left half.)

\_\_\_\_\_

To above result, apply reverse of initial permutation IP, which is  $IP^{-1}$ :

$IP^{-1}$							
4	1	3	5	7	2	8	6

This result is ciphertext. It is the S-DES encryption of the plaintext input.

-----